

UNIVERSITY OF TECHNOLOGY SYDNEY
Faculty of Engineering and Information Technology

**Stochastic Geometry Based Modeling and
Performance Analysis of Ultra-dense Cellular
Networks**

by

Junnan Yang

A THESIS SUBMITTED
IN PARTIAL FULFILLMENT OF THE
REQUIREMENTS FOR THE DEGREE

Doctor of Philosophy

Sydney, Australia

2019

Certificate of Authorship/Originality

I, Junnan Yang, certify that the work in this thesis has not been previously submitted for a degree nor has it been submitted as a part of the requirements for other degree except as fully acknowledged within the text.

I also certify that this thesis has been written by me. Any help that I have received in my research and in the preparation of the thesis itself has been fully acknowledged. In addition, I certify that all information sources and literature used are quoted in the thesis.

This research is supported by the Australian Government Research Training Program.

© Copyright 2019 Junnan Yang

Production Note:
Signature removed
prior to publication.

1 / 10 / 2019

ABSTRACT

Stochastic Geometry Based Modeling and Performance Analysis of Ultra-dense Cellular Networks

by

Junnan Yang

In the last decade, there has been an explosive increase in the demand for wireless network data traffic. To deal with such monumental consumer requirement for information communications, several notable technologies have been proposed, such as small cell networks (SCNs), device-to-device (D2D) communications.

In the first half of the thesis, we address the critical issue of interference management in the D2D enhanced cellular network. To reduce the severe interference caused by active D2D links, we consider a mode selection scheme based on the maximum received signal strength (MRSS) for each user equipment (UE) to control the D2D-to-cellular interference. This will mitigate the overlarge interference from the D2D links to the cellular links. Moreover, to improve the capacity of D2D-enhanced networks, we consider that the typical user is no longer a random user which is selected by a round-robin (RR) scheduler, as assumed in most studies in the literature. Instead, a cellular user with the maximum proportional fair (PF) metric is chosen by its serving BS as the typical user, which is referred to as the PF scheduler in the cellular tier. Furthermore, we quantify the performance gains brought by D2D communications in cellular networks and we find an optimum mode selection threshold to maximize the total area spectrum efficiency (ASE) in the network.

In the second half of the thesis, we adjust the antenna pattern to boost the area spectral efficiency (ASE) of cellular networks when considering the height of the base stations. Very recent studies have shown that the area spectral efficiency of downlink (DL) cellular networks will continuously decrease and finally crash to zero

as the base station (BS) density increases towards infinity if the absolute height difference between BS antenna and user equipment (UE) antenna is larger than zero. Such a phenomenon is referred to as the ASE Crash. We revisit this issue by considering optimizing the BS antenna downtilt in cellular networks. We investigated the relationship between the BS antenna downtilt and the downlink network performance in terms of the coverage probability and the ASE. Our results reveal a notable conclusion that there exists an optimal antenna downtilt to achieve the maximum coverage probability for each BS density. After applying the optimal antenna downtilt, the network performance can be significantly improved, and hence the ASE crash can be delayed by nearly one order of magnitude in terms of the BS density.

Dissertation directed by Professor Guoqiang Mao

School of Electrical and Data Engineering

Acknowledgements

The completion of this dissertation has been possible with the inspiration and encouragement from many people, to whom I am greatly indebted.

First of all, I should pay my immeasurable appreciation and deepest gratitude to my PhD supervisor Professor Guoqiang Mao and Dr. Ming Ding, for their never-ending guidance, strict requirements and clear training methods. These have helped me find a right way to do research and make great progress.

I feel extremely fortunate to be mentored by these two excellent scholars during my Ph.D. candidature. I will always remember their guidance and be grateful.

I am also grateful to other members in our research team, especially Dr. Jieqiong Chen, Dr. Tian Ding and Dr. Bin Yang, for making a friendly working environment, and for their support, great assistance and valuable advice to my research.

I also wish to express my gratitude to my friends who accompanied me during my studies. Dr. Shijin Li, Dr. Yifan Zuo, Dr. Lina Li, Dr. Rongrong Hu and Mr. Aaron Han, I will remember the times we spent together and hope that our friendship will last forever.

Finally, but mostly, I wish to express my deepest gratitude to My father Wanneng Yang, my mother Aisu Shen and my beloved wife Shuyun Sun. Although our family has experienced a very difficult period, you have given me tremendous support and encouragement so that I can successfully complete my work.

Junnan Yang
Sydney, Australia, 2019.

List of Publications

Journal Papers

- J-1. **Junnan Yang**, Ming Ding, Guoqiang Mao, Zihuai Lin and Xiaohu Ge, Analysis of Underlaid D2D-Enhanced Cellular Networks: Interference Management and Proportional Fair Scheduler, IEEE Access, Vol. 16, No. 3, pp. 1779-1791, 2019.
- J-2. **Junnan Yang**, Ming Ding, Guoqiang Mao, Zihuai Lin, De-gan Zhang, Tom Hao Luan, Optimal Base Station Antenna Downtilt in Downlink Cellular Networks, IEEE Transactions on Wireless Communications, Vol. 18, No. 3, pp. 1779-1791, March 2019.
- J-3. **Junnan Yang**, Ming Ding, Guoqiang Mao and Zihuai Lin, Interference Management in In-band D2D Underlaid Cellular Networks, accepted to IEEE Transactions on Cognitive Communications and Networking, May 2019.

Conference Papers

- C-1. **Junnan Yang**, Ming Ding, Guoqiang Mao and Tom H. Luan, Interference Management in Underlay In-band D2D-Enhanced Cellular Networks, in the 24th Asia-Pacific Conference on Communications, 2018. Invited Paper

Contents

Certificate	ii
Abstract	iii
Acknowledgments	v
List of Publications	vi
List of Figures	x
List of Tables	xiii
1 Introduction	1
1.1 Research Background	1
1.1.1 Ultra Dense Cellular Network	1
1.1.2 Device-to-Device Communications	3
1.2 Research Motivation	4
1.2.1 Network Modeling and D2D-Enhanced Network	4
1.2.2 Antenna Downtilt in UDN	5
1.3 Research Objectives and Contributions	6
1.4 Thesis Organization	10
2 Literature Review	11
2.1 Cellular Network Modeling using Stochastic Geometry	11
2.2 Device-to-Device Communications	19
2.3 Interference Management in Cellular Networks	21

3 Interference Management in D2D Underlaid Cellular Network	24
3.1 Introduction	25
3.2 System Model	26
3.2.1 D2D Network Model	27
3.2.2 User Mode Selection Scheme	29
3.3 Performance of the D2D Underlaid Cellular Network	32
3.3.1 User Mode Selection	32
3.4 Main Results	34
3.4.1 Percentage of UE operating in the cellular mode	34
3.4.2 Coverage Probability of D2D-Enhanced Cellular Network	38
3.5 Simulation and Discussion	47
3.5.1 Simulation setup	47
3.5.2 Validation of analytical results of $p^{\text{cov}}(\lambda, \gamma)$	48
3.5.3 Network Performance Without Interference Management	51
3.5.4 Discussion on the analytical results of ASE	52
3.6 Summary	53
4 Interference Management and Proportional Fair Scheduler in D2D Underlaid Cellular Network	55
4.1 Introduction	55
4.2 System Model	57
4.2.1 Scenario Description	58
4.2.2 Interference Management Scheme	59
4.2.3 BS Activation and UE Distribution	60

4.2.4	Proportional Fair Scheduler	62
4.3	Performance of the D2D Underlaid Cellular Network Using PF	64
4.3.1	User Mode Selection	65
4.3.2	Coverage Probabality	67
4.4	Simulation and Discussion	75
4.5	Summary	82
5	Optimal Antenna Downtilt in UDN	83
5.1	Introduction	83
5.2	System Model	83
5.2.1	Scenario Description	83
5.2.2	Path Loss Model	85
5.2.3	3D Antenna Pattern	87
5.2.4	User Association and Performance Metrics	87
5.3	Performance of the UDN Applying Antenna Downtilt	89
5.3.1	Coverage Probablity	89
5.3.2	Optimal Antenna Downtilt	96
5.4	Simulation and Discussion	105
5.5	Summary	114
6	Conclusion	115
	Bibliography	117

List of Figures

3.1	The probability for a UE to operate in the cellular mode vary the RSS threshold β , $P_B = 46\text{dBm}$	37
3.2	The D2D links distance (m) with simulation and using the second neighbor approximation.	44
3.3	The Coverage Probability $p^{\text{cov}}(\lambda, \gamma)$ vs. SINR threshold ($\lambda_{UE} = 200 \text{ UEs/km}^2$, $\lambda_{BS} = 5 \text{ UEs/km}^2$ and $\rho = 10\%$). The mode select threshold β is -50dBm	49
3.4	The Coverage Probability $p^{\text{cov}}(\lambda, \gamma)$ vs. β for 3GPP Case 1 ($\gamma_0 = 0 \text{ dB}$, $\lambda_{UE} = 200 \text{ UEs/km}^2$, $\lambda_{BS} = 5 \text{ UEs/km}^2$ and $\rho = 10\%$). . .	50
3.5	The coverage probability with and without the proposed interference management scheme ($\gamma_0 = 0 \text{ dB}$, $\lambda_{UE} = 300 \text{ UEs/km}^2$, $\lambda_{BS} = 5 \text{ UEs/km}^2$).	51
3.6	The ASE $A^{\text{ASE}}(\lambda, \gamma_0)$ vs. β for 3GPP Case 1 ($\gamma_0 = 0 \text{ dB}$, $\lambda_{UE} = 200 \text{ UEs/km}^2$, $\lambda_{BS} = 5 \text{ UEs/km}^2$ and $\rho = 10\%$).	52
4.1	The probability for a TU to operate in the cellular mode vary the RSS threshold β , $P_B = 24\text{dBm}$	66
4.2	The Coverage Probability $p_c^{\text{cov}}(\lambda, \gamma)$ vs. SINR threshold ($\lambda_b = 100 \text{ BSs/km}^2$, $\lambda_u = 300 \text{ UEs/km}^2$, $\lambda_{TU} = 150 \text{ UEs/km}^2$). . . .	77
4.3	The Coverage Probability of D2D tier vs. SINR threshold ($\lambda_b = 100 \text{ BSs/km}^2$, $\lambda_u = 300 \text{ UEs/km}^2$, $\lambda_{TU} = 150 \text{ UEs/km}^2$). . . .	78

4.4	The Coverage Probability $p^{\text{cov}}(\lambda, \gamma)$ vs. BS density ($\gamma_0 = 0$ dB, $\lambda_u = 300$ UEs/km ² , $\lambda_{TU} = 150$ UEs/km ² , $\beta=50$ dBm).	79
4.5	The ASE $A^{\text{ASE}}(\lambda, \gamma_0)$ vs. β ($\lambda_b = 100$ BSs/km ² , $\gamma_0 = 0$ dB, $\lambda_u = 300$ UEs/km ² , $\lambda_{Tu} = 150$ UEs/km ²).	80
5.1	An illustration of the 3D horizontal angle. The solid black dots indicate BSs, black arrows indicate the direction of the main beam for each sector.	84
5.2	An illustration of the 3D vertical angle.	85
5.3	The average signal and cumulative interference power with antenna downtilt and a BS density of 10BSs/km ²	98
5.4	Coverage probability vs. antenna downtilt of the LTE macrocell BS with $\gamma = 0$ dB.	106
5.5	Optimal antenna downtilt vs. base station density with $\gamma = 0$ dB. . .	107
5.6	The Performance Impact of BS deployment on the Coverage Probability with $\gamma = 0$ dB.	109
5.7	Optimal Antenna downtilt vs. BS density of the LTE picocell model with adopted path loss model and the simple path loss model.	109
5.8	Optimal Antenna downtilt vs. BS density 10 and 100 BSs/km ² of the LTE picocell model with adopted path loss model and the simple path loss model	110
5.9	The performance impact of BS antenna height on the coverage probability with $\gamma = 0$ dB.	111
5.10	Coverage probability vs. base station density with the optimal antenna downtilt and $\gamma = 0$ dB.	112
5.11	$A^{\text{ASE}}(\lambda, \gamma_0)$ vs. base station density with the optimal antenna downtilt and without antenna downtilt.	113

5.12	$A^{ASE}(\lambda, \gamma_0)$ vs base station density (Rayleigh fading for NLoS transmissions and Rician fading ($K = 10$) for LoS transmissions with $\gamma = 0\text{dB}$).	114
------	---	-----

List of Tables

2.1	A research map of Stochastic Geometry.	18
3.1	Notations	33
3.2	Notations	34
3.3	Simulation Parameters	48
4.1	Simulation Parameters	76